

Ordering Information - LC-030, -050, -075, -100, -150, -200

	Model	Frame Size	Coil Length	Winding Code	Cooling Option	Hall Feedback	Thermal Protection	Cable Length	UL Rated	Special Options
	LC-	030-	100-	D-	0-	T-	TR-	0-		
030										
050										
075										
100										
150										
200										
100	= 100mm									
200	= 200mm									
300	= 300mm									
400	= 400mm									
600	= 600mm									
800	= 800mm									
D										
E										
0	= None (Standard)									
T	= Trapezoidal Hall Effect									
0	= No Feedback									
TR	= PTC Thermal Sensor									
TS	= Thermal Switch									
0	= 300mm									
1	= 600mm									
2	= 1000mm									
Blank	= Not UL Rated									
UL	= UL Rated									
Blank	= Standard									

Magnet Track

	Model	Frame Size	Magnet Length	Cover	Special Options
	LCM-	030-	100-	C	
030					
050					
075					
100					
150					
200					
100	= 100mm				
250	= 250mm				
400	= 400mm				
500	= 500mm				
C	= Cover (Standard)				
Blank	= Standard				

Cooling Plate

	Model	Frame Size	Coil Length	Cooling
	LCCP-	030-	100-	AC
030				
050				
075				
100				
150				
200				
100	= 100mm			
200	= 200mm			
300	= 300mm			
400	= 400mm			
600	= 600mm			
800	= 800mm			
AC	= Air Cooling			
WC	= Water Cooling			

Cable Coding

	Color	Function
Motor Leads (Standard)	RED	ØU (A)
	WHT	ØV (B)
	BLK	ØW (C)
	GRN/YEL	GND
	BLK	TR (130°C)
Thermal Protection (Optional)	BLK	TR (130°C)
	BLU	TS (130°C)
	BLU	TS (130°C)
Trapezoidal Hall Effect (Optional)	RED	V+
	WHT	S1
	BLU	S2
	ORN	S3
	BLK	VRTN

Note: V+ = 5-24 Vdc

Motor and Hall effect cables are shielded.

All Specifications subject to change. Consult factory or website for latest specifications.

www.anorad.com www.rockwellautomation.com

Anorad Linear Motion Solutions Headquarters

Americas: Rockwell Automation, 100 Precision Drive, Shirley, NY, 11967-4710, USA, Tel: (1) 631.344.6600, Fax: (1) 631.344.6601

Europe: Rockwell Automation, De Dintel, 8-12, 5684 PS Best, The Netherlands, Tel: (31) 499 33 8585, Fax: (31) 499 33 8580

Japan: Rockwell Automation, 6-5, Nishiki 1-chrome, Naka-ku, Nagoya 460-0003, Japan, Tel: +81.52.222.7060, Fax: +81.52.222.7065

Korea: Rockwell Automation, 16F, 17F Samhwa Bld., 144-17, Samsung-dong, Gangnam-gu, Seoul, Korea 135-280, Tel+82.2.2188.4400, Fax: +82.2.564.8760

Power, Control and Information Solutions Headquarters

Americas: Rockwell Automation, 1201 South Second Street, Milwaukee, WI 53204-2496 USA, Tel: (1) 414.382.2000, Fax: (1) 414.382.4444

Europe/Middle East/Africa: Rockwell Automation, Vorstlaan/Boulevard du Souverain 36, 1170 Brussels, Belgium, Tel: (32) 2 663 0600, Fax: (32) 2 663 0640

Asia Pacific: Rockwell Automation, Level 14, Core F, Cyberport 3, Cyberport Road, Hong Kong, Tel: (852) 2887 4788, Fax: (852) 2508 1846